



K. LACEY WIRES AND CABLES

D10 TELEPHONE CABLE, MARK 4

DOUBLE INSULATED 7/0.28 TWISTED PAIR BLACK/BLACK

MANUFACTURED TO DEF 61-12 PT 12 SECTION 3 ISSUE 1
NATO STOCK NUMBER : 6145-99-648-0813

CONSTRUCTION

7/0.28MM Conductor, 4 Copper wires, 3 Galvanised Steel wires
 Centre strand copper, outer alternate strands of copper and galvanised steel

Each conductor insulated with Polyethylene (0.48mm nom. wall)

Sheath (secondary) insulation of Nylon (0.17mm nom. wall)

Cores laid up as per above @ 125mm right hand lay

SPECIFICATION

DEF 61-12 PART 12 SECTION 3 ISSUE 1

SCOPE

Temperature Rating -40°C to +70°C

Conductor Resistance 151Ω/Loop Km MAXIMUM @ 20°C

Insulation Resistance 3500MΩ/Km MINIMUM @ 20 ± 5°C

Conductor				Finished Cable	
Strand mm	Dia. Nom. mm	Dia. Nom. Mm Over Ins.	Dia. Nom. mm over sheath	O/Dia. Nom. mm	Weight Kgs / km
7/0.28	2.21	1.80	2.14	4.28	18.86

CONTACT US NOW FOR A QUOTATION

Tel. +44 (0) 1903 771336 Fax. +44 (0) 1903 772120 Email. sales@klaceycables.co.uk

INFORMATION GIVEN IS BASED ON GENERAL EXPERIENCE ONLY AND IS GIVEN IN GOOD FAITH. NO WARRANTY IS GIVEN WITH RESPECT TO THE INFORMATION AND USERS MUST DETERMINE THE SUITABILITY OF THE PRODUCT PRIOR TO ANY PARTICULAR USE.

BS EN 9120:2005, ISO 9001:2008 APPROVED BSI. RS000146 BAE APPROVED