



**K. Lacey**  
ENGINEERS & DESIGNERS LIMITED

Unit 4 • Brookside Avenue Trading Estate • Rustington • West Sussex • BN16 3LF  
Tel. +44 (0)1903 771336 • Fax. +44 (0)1903 772120 • Email. sales@klaceycables.co.uk

# D10 TELEPHONE CABLE, MARK 4

## DOUBLE INSULATED 7/0.28 TWISTED PAIR BLACK/BLACK

**MANUFACTURED TO DEF 61-12 PT 12 SECTION 3 ISSUE 1  
NATO STOCK NUMBER : 6145-99-648-0813**

### CONSTRUCTION

7/0.28MM Conductor, 4 Copper wires, 3 Galvanised Steel wires  
Centre strand copper, outer alternate strands of copper and galvanised steel

Each conductor insulated with Polyethylene (0.48mm nom. wall)

Sheath (secondary) insulation of Nylon (0.17mm nom. wall)

Cores laid up as per above @ 125mm right hand lay

### SPECIFICATION

DEF 61-12 PART 12 SECTION 3 ISSUE 1

### SCOPE

Temperature Rating -40°C to +70°C

Conductor Resistance 151Ω/Loop Km MAXIMUM @ 20°C

Insulation Resistance 3500MΩ/Km MINIMUM @ 20 ± 5°C

Conductor				Finished Cable	
Strand mm	Dia. Nom. mm	Dia. Nom. Mm Over Ins.	Dia. Nom. mm over sheath	O/Dia. Nom. mm	Weight Kgs / km
7/0.28	2.21	1.80	2.14	4.28	18.86

---

## CONTACT US NOW FOR A QUOTATION

Tel. +44 (0) 1903 771336 Fax. +44 (0) 1903 772120 Email. sales@klaceycables.co.uk

INFORMATION GIVEN IS BASED ON GENERAL EXPERIENCE ONLY AND IS GIVEN IN GOOD FAITH. NO WARRANTY IS GIVEN WITH RESPECT TO THE INFORMATION AND USERS MUST DETERMINE THE SUITABILITY OF THE PRODUCT PRIOR TO ANY PARTICULAR USE.