



KP260

MANUFACTURED TO BRAND-REX SPECIFICATION HPECM44

CONSTRUCTION

Nickel Plated Copper Wire Conductor (24AWG is Nickel Plated Copper Alloy).
Polyimide/FEP taped insulation with taped PTFE finish.

SPECIFICATION

Brand-Rex HPECM44

SCOPE

Operating Temperature from -65°C to +260°C.
600V(r.m.s.) @ 2000Hz

Size AWG	Conductor			Finished Cable			
	Strand mm	Nom. Dia. mm	Max. Resistance @ 20°C Ohm / km	O/Dia. Min. mm	O/Dia. Max. mm	AMP Rating	Max. Weight Kg / Km
24	19/0.12	0.56	114.70	0.98	1.16	6.50	3.55
22	19/0.15	0.74	58.80	1.10	1.32	9.00	4.90
20	19/0.20	0.96	32.80	1.35	1.55	13.00	7.70
18	19/0.25	1.21	20.80	1.60	1.80	17.00	11.30
16	19/0.30	1.44	14.40	1.80	2.05	21.00	15.80
14	37/0.25	1.71	10.60	2.10	2.40	27.00	21.00
12	37/0.32	2.15	6.60	2.50	2.90	35.00	32.00
10	37/0.40	2.74	4.13	3.20	3.70	44.00	53.00
8	119/0.30	4.20	2.40	4.80	5.30	63.00	93.00
6	182/0.30	5.15	1.57	5.80	6.30	96.00	140.00
4	294/0.30	6.60	0.971	7.10	7.70	140.00	217.00
2	203/0.45	8.30	0.606	8.80	9.40	195.00	330.00
1	245/0.45	9.35	0.50	9.70	10.40	220.00	400.00
0	322/0.45	10.50	0.381	10.90	11.70	260.00	525.00
00	420/0.45	11.80	0.290	12.30	13.20	300.00	680.00
000	518/0.45	13.40	0.237	14.00	14.80	345.00	835.00
0000	665/0.45	14.80	0.190	15.60	16.40	380.00	1060.00

Also Available :-

Multicore – Comprising of single core cables twisted together
2 core (red/blue), 3 core (red/blue/yellow), 4 core (red/blue/yellow/green).

Screened and Jacketed – Comprising of single or multicore cables with a collective Nickel plated copper wire braid, Polyimide/FEP tape and an outer jacket of taped PTFE.

Please request further information if required

CONTACT US NOW FOR A QUOTATION

Tel. +44 (0) 1903 771336 Fax. +44 (0) 1903 772120 Email. sales@klaceyables.co.uk

INFORMATION GIVEN IS BASED ON GENERAL EXPERIENCE ONLY AND IS GIVEN IN GOOD FAITH. NO WARRANTY IS GIVEN WITH RESPECT TO THE INFORMATION AND USERS MUST DETERMINE THE SUITABILITY OF THE PRODUCT PRIOR TO ANY PARTICULAR USE.