



K. LACEY WIRES AND CABLES

PT 17 DEMOLITION CABLE

0.75MM

(For Detonator Firing Circuits)

MANUFACTURED TO DEF 61-12 PT 17 / 1
NATO STOCK NUMBER : 6145-99-017-3378

CONSTRUCTION

24/0.20mm (0.75mm²) Annealed Copper Conductor

Conductor insulated with PVC

2 x Conductor twisted together (twisted twin). 1 Brown, 1 Black

SPECIFICATION

DEF 61-12 PART 17 ISSUE 1

Conductor					Finished Cable
No. of Strands	Strand Dia mm	Insulation Thickness Nom. mm	Dia. Nom. mm	Mean O/Dia. of each core mm	Nominal Diameter over sheath. mm
24	0.2	0.65	2.44	Lower Limit 2.39 Upper Limit 2.49	4.88

CHARACTERISTICS

Voltage Rating : 300/500V

RDC : 26 ohms/km@20 °C

CONTACT US NOW FOR A QUOTATION

Tel. +44 (0) 1903 771336 Fax. +44 (0) 1903 772120 Email. sales@klaceycables.co.uk

INFORMATION GIVEN IS BASED ON GENERAL EXPERIENCE ONLY AND IS GIVEN IN GOOD FAITH. NO WARRANTY IS GIVEN WITH RESPECT TO THE INFORMATION AND USERS MUST DETERMINE THE SUITABILITY OF THE PRODUCT PRIOR TO ANY PARTICULAR USE.

BS EN 9120:2005, ISO 9001:2008 APPROVED BSI. RS000146 BAE APPROVED