



K. LACEY WIRES AND CABLES

EFWRAP

EXTENSIBLE PTFE SPIRAL WRAP

PERFORMANCE CHARACTERISTICS

Maximum Service Temperature +250°C
 Minimum Service Temperature -75°C
 (-60°C if flexed continuously)

PROPERTIES

Flexible throughout temperature range
 Resistant to flames and smoke emission,
 Will not support combustion
 Resistant to scrape abrasion and cutting
 Standard Colour ; Black

SPECIFICATION

BICC EC63

Meets Airbus AS41088



SIZE RANGE

Ref.	Nominal Size Of Wrap:			
EFWRAP	Internal Dia.	O/All Width	Thickness	Approx Dia of Beaded edge
	mm	mm	mm	mm
03.00	03.00	05.00	0.75	1.00
05.00	05.00	05.00	0.75	1.00
07.50	07.50	08.00	0.75	1.00
12.50	12.50	10.00	0.75	1.00
25.50	25.50	12.50	1.25	1.60

Efwrap will return to its original spiral form after being extended and when applied to looms of wire, it grips and holds the wires in place and also obviates the risk of damage caused by tight lacings.

Efwrap is clean to handle and remains unaffected by most chemicals.

The temperature range, chemical and physical properties of Efwrap provides a taped cable sheath giving looms added protection against high temperatures when properly installed.

The beaded edges of Efwrap prevent chafing or damage to the insulation if branch wires are taken out of the loom. They also reduce the risk of sharp edges displacing the wrap and causing damage to the cables underneath. Efwrap can be used again many times making it an economical to use product.

CONTACT US NOW FOR A QUOTATION

Tel. +44 (0) 1903 771336 Fax. +44 (0) 1903 255411 Email. sales@klaceyables.co.uk

INFORMATION GIVEN IS BASED ON GENERAL EXPERIENCE ONLY AND IS GIVEN IN GOOD FAITH. NO WARRANTY IS GIVEN WITH RESPECT TO THE INFORMATION AND USERS MUST DETERMINE THE SUITABILITY OF THE PRODUCT PRIOR TO ANY PARTICULAR USE.

BS EN 9120:2005, ISO 9001:2008 APPROVED BSI. RS000146 BAE APPROVED