



K. LACEY WIRES AND CABLES

FEPSIL

MANUFACTURED TO HSAL/92/2020

CONSTRUCTION

Nickel Plated Copper Wire Conductor. Silicone Insulated (White). Glass Braid with Green Lacquer. Clear FEP Sheath.

SPECIFICATION

HSAL/92/2020 BRAND-REX

SCOPE

Operating Temperature from -75°C to +190°C.
Voltage Rating 600V (r.m.s.) at 1600Hz.

Size AWG	Conductor				Cable	
	Area mm ²	Strand mm	Dia. Nom. mm	Max. Resistance @20°C Ω / km	O/Dia. Nom. mm	Max. Weight. Kg/Km
22	0.336	19/0.150	00.75	61.3	02.20	10.00
20	0.597	19/0.200	01.00	33.60	02.46	13.00
18	0.933	19/0.250	01.25	21.20	02.84	18.00
16	1.340	19/0.300	01.50	14.60	03.14	22.00
14	1.820	37/0.250	01.75	10.70	03.67	33.00
12	2.890	37/0.320	02.21	06.44	04.17	46.00
10	4.650	37/0.400	02.80	04.08	04.94	70.00
8	8.410	119/0.30	04.23	02.28	06.18	116.00
6	12.850	182/0.30	05.28	01.49	07.72	176.00

NOTE :

These cables are manufactured with metric conductors, identical to those used in manufacturing Uniefglas metric BSG 222. With this exception Fepsil Metric fully meets the dimensional and performance requirements of BSG 206. BSG 206 (imperial) is no longer manufactured.

CONTACT US NOW FOR A QUOTATION

Tel. +44 (0) 1903 771336 Fax. +44 (0) 1903 772120 Email. sales@klaceycables.co.uk

INFORMATION GIVEN IS BASED ON GENERAL EXPERIENCE ONLY AND IS GIVEN IN GOOD FAITH. NO WARRANTY IS GIVEN WITH RESPECT TO THE INFORMATION AND USERS MUST DETERMINE THE SUITABILITY OF THE PRODUCT PRIOR TO ANY PARTICULAR USE.

BS EN 9120:2005, ISO 9001:2008 APPROVED BSI. RS000146 BAE APPROVED