



K. LACEY WIRES AND CABLES

DEMOLITION CABLE 0.22MM

(For Detonator Firing Circuits)

CONSTRUCTION

7/0.20mm (0.22mm²) Plain Annealed Copper Conductor

Conductor insulated with PVC

2 x Conductor twisted together (twisted twin). 1 Brown, 1 Black. No Sheath.

Voltage Rating : 300/500V

SPECIFICATION

Similar to DEF 61-12 PART 17

Conductor					Finished Cable			
No. of Strands	Strand Dia mm	Insulation Thickness Nom. mm	Dia. Nom. mm	Mean O/Dia. of each core mm	Nominal Diameter over sheath. mm	Conductor DC Resistance @ 20°C	Ins. Resistance @ 20°C	Approx Weight Kg/Km
7	0.2	0.3	1.20	Lower Limit 1.17 Upper Limit 1.23	2.40	92 ohm/km	20Mohm/km	15

CONTACT US NOW FOR A QUOTATION

Tel. +44 (0) 1903 771336 Fax. +44 (0) 1903 255411 Email. sales@klaceyables.co.uk

INFORMATION GIVEN IS BASED ON GENERAL EXPERIENCE ONLY AND IS GIVEN IN GOOD FAITH. NO WARRANTY IS GIVEN WITH RESPECT TO THE INFORMATION AND USERS MUST DETERMINE THE SUITABILITY OF THE PRODUCT PRIOR TO ANY PARTICULAR USE.