



K. LACEY WIRES AND CABLES

PTFE TIE CORDS AND LACING TAPES

Product Description

Braided Circular Tie Cords and Flat Lacing Tapes
 Braided PTFE coated glass yarn giving superior strength and flex life.
 Negligible shrinkage or stretching

Characteristics

Operating Temperature -55 to +260 °C
 Non-burning and Chemically Resistant

Availability

Colour White as standard, other colours upon request

Applications

Typical applications for tying of wiring harnesses in aerospace applications and suspending any product in hazardous environments such as plating tanks, impregnation and encapsulation

PTFE TIE CORDS (CIRCULAR CROSS SECTION)

TYPE	NOM DIA (MM)	APPROX. YIELD (M/KG)	NOM. TENSILE STRENGTH (KG)	APPROX. WEIGHT (KG/KM)
C037	0.90	1030	13	0.971
C045	1.10	680	22	1.470
C085*	2.00	210	80	4.760

*included in the construction C085 is a centre strengthening cord

PTFE LACING TAPES (FLAT CROSS SECTION)

TYPE	NOM DIA (MM)	APPROX. YIELD (M/KG)	NOM. TENSILE STRENGTH (KG)	APPROX. WEIGHT (KG/KM)
+T070	1.78	1000	16	1.000
+T085	2.16	660	20	1.515
T100	2.60	620	20	1.613
+T120	3.05	455	24	2.200

+T070, T085 AND T120 ARE APPROVED TO **PAN6481A**

CONTACT US NOW FOR A QUOTATION

Tel. +44 (0) 1903 771336 Fax. +44 (0) 1903 255411 Email. sales@klaceyables.co.uk

INFORMATION GIVEN IS BASED ON GENERAL EXPERIENCE ONLY AND IS GIVEN IN GOOD FAITH. NO WARRANTY IS GIVEN WITH RESPECT TO THE INFORMATION AND USERS MUST DETERMINE THE SUITABILITY OF THE PRODUCT PRIOR TO ANY PARTICULAR USE.

AS9120 Rev A and ISO9001:2008 APPROVED BSI. RS000146 BAE APPROVED