



K. LACEY WIRES AND CABLES

Coaxial Types - T3263 & T3264

50ohm RF Coaxial Cable

CONSTRUCTION

Inner Conductor : Solid Silver coated copper covered steel wire

Dielectric : Solid extruded PTFE

Outer Conductor : Single silver coated copper wire braid

Jacket : Light Blue FEP

SPECIFICATION

Brand Rex unique specification T3263/T3264

SCOPE

Voltage Rating ... (maximum continuous working) 900V r.m.s

Maximum conductor Operating Temperature ... -55°C to +200°C

Impedance ... 50Ω

Type	Conductor		Screen	Finished Cable		
	Strand mm	Dia. Over dielectric (mm)	Dia. over outer conductor	Nom. Overall Dia. (mm)	Weight kg/km	Minimum Bend Radius (mm)
T3263	1/0.315	0.91	1.41	1.93	10.00	13
T3264	1/0.455	1.50	1.93	2.50	16.00	15

CONTACT US NOW FOR A QUOTATION

Tel. +44 (0) 1903 771336 Fax. +44 (0) 1903 255411 Email. sales@klaceyables.co.uk

INFORMATION GIVEN IS BASED ON GENERAL EXPERIENCE ONLY AND IS GIVEN IN GOOD FAITH. NO WARRANTY IS GIVEN WITH RESPECT TO THE INFORMATION AND USERS MUST DETERMINE THE SUITABILITY OF THE PRODUCT PRIOR TO ANY PARTICULAR USE.